




	A	B	C
1		<b>Arista Networks</b>	
2		5453 Great America Parkway, Santa Clara, CA 950541 U.S.A.	
3		+1(408)547-5500 <a href="https://www.arista.com/en/">https://www.arista.com/en/</a>	
4		Contact <a href="mailto:info@arista.com">info@arista.com</a>	
5		<b>Product 1 (Low End)</b>	<b>Product 2 (High End)</b>
6	<b>Model</b>	<b>Arista 7260QX3 (or scaled variant)</b>	<b>Arista 7260CX3-64</b>
7	<b>Overview</b>	<b>High-performance 40/100G Data Center Leaf/Spine Switch, 2RU form factor</b>	<b>High-density 100G Data Center Leaf/Spine Switch, 2RU form factor</b>
8	<b>Picture</b>		
9	<b>Hardware Version</b>	Rev X3	Rev X3
10	<b>DnLink Ports</b>	<b>Up to 32 x 40/100 GbE QSFP+ (breakout capable)</b>	<b>64 x 100 GbE QSFP28</b>
11	<b>COMBO Ports</b>	N/A	N/A
12	<b>UpLink Ports</b>	Shared (all QSFP+)	Shared (all QSFP28)
13	<b>Port Standards &amp; Functions</b>	IEEE 802.3 100BASE-X / 1000BASE-X / 10GBASE-R / 25GBASE-R / 40GBASE-R	IEEE 802.3 100BASE-X / 1000BASE-X / 10GBASE-R / 25GBASE-R / 40GBASE-R
14		IEEE 802.3 100GBASE-R	IEEE 802.3 100GBASE-R
15		IEEE 802.3by 25 GbE, 802.3bj 100 GbE Backplane	IEEE 802.3by 25 GbE, 802.3bj 100 GbE Backplane
16		IEEE 802.1p Priority Queues	IEEE 802.1p Priority Queues
17		IEEE 802.1Q VLAN Tagging	IEEE 802.1Q VLAN Tagging
18		IEEE 802.3x Flow Control	IEEE 802.3x Flow Control
19		IEEE 802.1ab LLDP	IEEE 802.1ab LLDP
20		802.3ad Link Aggregation (LACP)	802.3ad Link Aggregation (LACP)
21	802.1ax Link Aggregation Control	802.1ax Link Aggregation Control	
22	802.1D / 802.1w Spanning Tree Protocols	802.1D / 802.1w Spanning Tree Protocols	
23	<b>Network Cables</b>	SMF/MMF based on QSFP+ transceivers	SMF/MMF based on QSFP28 transceivers
24	<b>Duplex Mode</b>	Full Duplex only	Full Duplex only
25	<b>Media Interface Exchange</b>	Auto Negotiation & Optic Detection	Auto Negotiation & Optic Detection
26	<b>Switching Capacity</b>	Up to 6.4 Tbps bidirectional	6.4 Tbps bidirectional
27	<b>Packet Forwarding</b>	Up to 2.6 Bpps	Up to 2.6 Bpps
28	<b>Transmission Method</b>	Store-and-Forward	Store-and-Forward
29	<b>MAC Address Table</b>	Up to 288K entries	Up to 288K entries
30	<b>Static MAC Addresses</b>	Supported via EOS configuration	Supported via EOS configuration
31	<b>Max. 64 Byte Packet Fwd Rate</b>	Up to 2.6 Bpps	Up to 2.6 Bpps
32	<b>Packet Buffer Memory</b>	42 MB dynamic shared	42 MB dynamic shared
33	<b>Management Interfaces</b>	RJ-45 Console, USB, Out-of-Band Mgmt Port	RJ-45 Console, USB, Out-of-Band Mgmt Port
34	<b>CPU</b>	Multi-core Intel Xeon	Multi-core Intel Xeon
35	<b>CPU Memory</b>	32 GB DDR4	32 GB DDR4
36	<b>Flash Memory</b>	128 GB SSD	128 GB SSD
37	<b>L3 (Layer 3) Routing</b>	Full IPv4/IPv6, OSPF, BGP, IS-IS, EVPN VXLAN	Full IPv4/IPv6, OSPF, BGP, IS-IS, EVPN VXLAN
38	<b>240/4 Compatibility</b>	EOS 4.32 / CloudVision 2026 (4.35+ supported)	EOS 4.32 / CloudVision 2026 (4.35+ supported)

	A	B	C
39	<b>Power over Ethernet (PoE)</b>	<b>Arista 7260QX3 (or scaled variant)</b>	<b>Arista 7260CX3-64</b>
40	PoE Standards	N/A	N/A
41	PoE Capable Ports	N/A	N/A
42	PoE Power Budget	N/A	N/A
43	<b>LEDs</b>	<b>Arista 7260QX3 (or scaled variant)</b>	<b>Arista 7260CX3-64</b>
44	Power (per device)	Yes	Yes
45	Console (per device)	Yes	Yes
46	Link/Activity/Speed (per port)	Yes	Yes
47	PWR Max	—	—
48	Fan Error	—	—
49	<b>Physical &amp; Environmental</b>	<b>Arista 7260QX3 (or scaled variant)</b>	<b>Arista 7260CX3-64</b>
50	Power Input	Dual Hot-swap AC/DC PSUs	Dual Hot-swap AC/DC PSUs
51	Max. Power Consumption (PoE enabled)	N/A	N/A
52	Max. Power Consumption (PoE disabled)	~1000 W typical / 1300 W max	~1200 W typical / 1500 W max
53	Standby Power Consumption	~250 W idle	~300 W idle
54	Acoustics	~62 dB(A)	~65 dB(A)
55	Heat Dissipation	~3500 BTU/hr	~4000 BTU/hr
56	Fans	N+1 Redundant Smart Fans	N+1 Redundant Smart Fans
57	Operating Temperature	0 °C – 40 °C (32 °F – 104 °F)	0 °C – 40 °C (32 °F – 104 °F)
58	Storage Temperature	-40 °C – 70 °C (-40 °F – 158 °F)	-40 °C – 70 °C (-40 °F – 158 °F)
59	Operating Humidity	5 % to 95 %, non-condensing	5 % to 95 %, non-condensing
60	Storage Humidity	5 % to 95 %, non-condensing	5 % to 95 %, non-condensing
61	Dimensions (W x D x H)	19" × 18" × 3.5" (2RU) ≈ 48.3 × 45.7 × 8.9 cm	19" × 18" × 3.5" (2RU) ≈ 48.3 × 45.7 × 8.9 cm
62	Weight	~35 lb (16 kg)	~34 lb (15.4 kg)
63	Protection Grade	Standard data-center enclosure	Standard data-center enclosure
64	MTBF	> 200,000 hours	> 200,000 hours
65	Warranty	Limited 1-Year Hardware / Software Support	Limited 1-Year Hardware / Software Support
66	EMI Certifications	FCC Class A, ICES-003, VCCI, CE EN55032	FCC Class A, ICES-003, VCCI, CE EN55032
67	Safety Certifications	UL/CSA 60950-1 and 62368-1 compliant	UL/CSA 60950-1 and 62368-1 compliant
68	Option 1	—	—
69	Option 2	—	—
70	<b>Price/Unit</b>	<b>Arista 7260QX3 (or scaled variant)</b>	<b>Arista 7260CX3-64</b>
71	Sample	—	—
72	500pcs	—	—
73	1K	—	—
74	Packaging	1 × Main Unit, 2 × PSUs, Rack-mount Kit, Console Cable	1 × Main Unit, 2 × PSUs, Rack-mount Kit, Console Cable
75	Specifications	<a href="https://www.arista.com/en/products/7060x-series">https://www.arista.com/en/products/7060x-series</a> (datasheet)	<a href="https://www.arista.com/en/products/7060x-series">https://www.arista.com/en/products/7060x-series</a> (datasheet)
76	Payment term	100 % T/T in advance	